



**Pompa a 3 pistoni in ceramica, sistema biella/ manovella con testata in ottone. Motore 1400 giri servizio continuo a 4 poli, con protezione termica.**

**Pump with 3 ceramic pump with ceramic pistons (rod/crank system) 4 pole electric motor (1400Rpm), continuous duty with overload thermal switch.**

## **IDROPULTRICI AD ALTA PRESSIONE A FREDDO**

- Compatta e maneggevole
- Testata ottone
- Trasmissione motore-pompa diretta
- Aspirazione detergente in bassa pressione con dosatore e filtro
- Telaio in acciaio verniciato con polveri epossidiche
- Valvola di regolazione con azzeramento pompa
- Manometro controllo pressione
- Carenatura in materiale plastico rinforzato.

## **COLD WATER PROFESSIONAL HIGH PRESSURE CLEANER- EASY TO USE**

- Simple and versatile solution
- Brass head
- Motor-pump direct transmission
- Detergent suction in low pressure with metering system and filter
- Steel frame painted with epoxy powders
- Regulation valve with pump set to zero
- Pressure gauge
- Reinforced plastic cover

Modello Model	Codice Code	Pressione (Bar) Pressure (Bar)		Pressione Max Max Pressure		Vollaggio Voltage	Potenza Power		Peso Weight	Dimensioni Dimensions
		NOM	MAX	L/MIN	L/H		VOLT/HZ/RPM	KW		
MEC 100.12	10.04.02100	100	110	12	720	230/50/1450	2,2	3	47	60x50x78
MEC 140.10	10.04.03200	140	150	10	600	230/50/1450	2,2	3	47	60x50x79
MEC 150.14	10.04.01400	150	165	14	840	400/50/1450	4	5,5	48	60x50x80
MEC 150.15	10.04.01500	150	165	15	900	400/50/1450	4	5,5	48	60x50x80
MEC 170.13	10.04.02300	170	180	13	780	400/50/1450	4	5,5	49	60x50x80

### **DOTAZIONE STANDARD / STANDARD EQUIPMENT**



**1 TUBO PROFESSIONALE R1 DA MT 10**  
**1 R1 10 MT HOSE**



**1 UGELLO-LANCIA**  
**1 HP NOZZLE**



**1 GUN WITH HANDLE**  
**1 LANCE EXTENSION**